

*** SPARE PART*** SIMATIC PANEL OP170B BLUE MODE STN
 DISPLAY MPI-/PROFIBUS-DP INTERFACE PRINTER INTERFACE
 SLOT FOR CF-CARD CONFIGURABLE WITH PROTOOL/LITE
 FROM VERSION V5.2+SP2



Display	
Design of display	STN, 4 blue levels
Screen diagonal	5.7 in
Resolution (pixels)	
• Horizontal image resolution	320 Pixel
• Vertical image resolution	240 Pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Membrane keyboard
Keyboard fonts	
• Membrane keyboard	Yes
— user-definable label membrane keys	Yes
• Function keys	
— Number of function keys	24
— Number of function keys with LEDs	18
• System keys	
— Number of system keys	35

• Numeric keyboard	Yes
• alphanumeric keyboard	Yes
• hexadecimal keyboard	Yes
• Multi-key operation	Yes

Connection type

• Connection for mouse/keyboard/barcode reader	- / - / -
--	-----------

Installation type/mounting

Mounting position	vertical
maximum permissible angle of inclination without external ventilation	35°

Supply voltage

UPS connectable (serial)	No
--------------------------	----

Input current

Current consumption (rated value)	0.25 A
-----------------------------------	--------

Power

Active power input, typ.	6 W
--------------------------	-----

Processor

Processor type	RISC 32-bit, 66 MHz
----------------	---------------------

Drives

Diskette drive	No
CD-ROM	No
Hard disk	No

Memory

Type of memory	Flash / RAM
Memory available for user data	768 kbyte

Type of output

Info LED	Yes
Power LED	No
Error LED	No

Time of day

Clock	
• Type	Software clock, synchronizable, no battery backup
• retentive	No
• synchronizable	Yes

Interfaces

Interfaces/bus type	TTY optional, 2 x RS232, 1 x RS422, 1 x RS485 (max. 12 Mbit/s)
Number of RS 485 interfaces	1
• Transmission rate, max.	12 Mbit/s

CF card slot	1 x CF card slot
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
Standards, approvals, certificates	
Certifications	CE, FM Class I Div. 2, UL, CSA
Ambient conditions	
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	85 %
Operating systems	
pre-installed operating system	Windows CE
Configuration	
Configuration software	
• Configuration tool	ProTool / Lite, Version 5.2 SP 2 or higher or WinCC flexible Compact Version 2004 or higher (to be ordered separately)
Languages	
Online languages	
• Number of online/runtime languages	5
Project languages	
• Languages per project	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Task planner	Yes
Help system	Yes
• Number of characters per info text	70
• Number of tooltips	0
Message system	
• Number of alarm classes	32
• Number of messages	2 000
• Bit messages	Yes
— Number of bit messages	2 000
• Analog messages	Yes
— Number of analog messages	2 000
• Telegram message procedure Alarm S	No
• System messages HMI	Yes
• System messages PLC	No

• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	No
• Lines	1
• Number of characters per message	80
• Number of process values per message	8
• Acknowledgment groups	
— Number of acknowledgement groups	99
• Message indicator	Yes
• acoustic feedback	No
• First/last value	Yes
Recipe management	
• Number of recipes	100
• Data records per recipe	200
• Entries per data record	200
• Recipe memory	32 KB integrated Flash, expandable
Variables	
• Number of variables per device	1 000
• Number of variables per screen	50
• Number of variables	1 000
• Initial values	1 000
• Type Date & Time	1 000
• Limit values	Yes
• Multiplexing	Yes
• Structures	No
Images	
• Number of configurable images	100
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	2,000 text elements
• Number of I/O fields per image	0
• Number of date/time fields	30
• Index of screen context	No
• Return	Yes
• Graphics object	Bit maps, icons, icon (full-screen)
— Icons	500
— Icon (full screen)	50
Complex image objects	
• Status/control	Not possible

- dynamic objects
 - Number of objects per project 500
 - Number of curve diagrams per image 5
- Methods Trend
- Bar graphs
 - Number of bars per chart 5
- Sliders
 - Number of slides per image 0
- Pointer instruments
 - Number of analog indicators per image 0
- Limit value lines Yes
- Number of alphanumeric fields 1 000
 - alphanumeric fields per image 100
- Number of numerical fields 1 000
 - numerical fields per image 100
- Number of password fields 1 000
- Number of visible switches per project 1 000
 - visible switches per image 100
 - hidden switches per image 100
- Number of status switches per project 1 000
 - Number of status switches per image 100
- Number of selector switches per project 1 000
 - Selector switches per image 100
- Number of decade switches per project 0
 - Decade switches per image 0
- Number of signal lamps per project 1 000
 - Signal lamps per image 100

Diagrams, bar graphs, invisible buttons

500
5
Trend
5
0
0
Yes
1 000
100
1 000
100
1 000
1 000
100
100
1 000
100
1 000
100
0
0
1 000
100

Attributes for dynamic objects

- Color change Yes
- X/Y movement Yes
- Hide Yes
- Angle of rotation No

Lists

- Number of text lists per project 300
- Number of text lists per image 10
- Number of entries per text list 256
- Number of graphics lists per project 100
- Number of graphic lists per image 10
- Number of entries per graphics list 255

Security

- Number of user groups 10

• Password export/import	Yes
Data carrier support	
• PC card	No
• CF card	Yes
• Diskette drive	No
• Hard disk	No
• CD-ROM	No
Logging through printer	
• Recording/Printing	Alarms, report (shift report)
Transfer (upload/download)	
• Transfer of configuration	MPI/PROFIBUS DP, serial, automatic transfer recognition
Process coupling	
• Connection to controller	S5, S7-200, S7- 300/400, TI 505, Win AC, SINUMERIK, SIMOTION, Allen Bradley (DF1), Mitsubishi (FX), Telemecanique (ADJUST), Modicon (Modbus), for further non-Siemens drivers, see section on "System interfaces"
• S7-200	Yes
— PPI (point-to-point)	Yes
— PPI network	No
— MPI	Yes
— PROFIBUS DP	Yes
• S7-300/400	Yes
— MPI	Yes
— PROFIBUS DP	Yes
— PROFINET	No
• S5	Yes
— serial	Yes
— PROFIBUS DP	Yes
• TI 505	Yes
• Allen Bradley (DF1)	Yes
• Allen Bradley (DF485)	No
• Mitsubishi (FX)	Yes
• Mitsubishi (MP4)	Yes
• Telemecanique (ADJUST)	Yes
• Telemecanique (Uni-Telway)	Yes
• OMRON (LINK/Multilink)	No
• Modicon (Modbus)	Yes
• GE-Fanuc (SNP)	Yes
Functions	
• Key repeat	No
• TAB sequence	Yes
• Calculating functions	Yes

• Animate	Yes
• Menu tree editor	No
• Unit switchover	No
Service tools/configuration aids	
• Clean screen	No
• Touch calibration	No
• Backup/Restore manually	Yes
• Simulation	Yes
• Device switchover	Yes
• Delta transfer	Yes
• Monitoring function for battery and memory	Yes
• Trace (operation archive)	No
Expandability/openness	
• Open Platform Program	Yes
Peripherals/Options	
Peripherals	Printer
• SIMATIC HMI MM memory card: Multi Media Card	No
• SIMATIC HMI SD memory card: Secure Digital memory card	No
• USB memory	No
Dimensions	
Width of the housing front	240 mm
Height of housing front	252 mm
Overall depth	45 mm
Weights	
Weight (without packaging)	0.9 kg
Other	
free hotline	Yes
Warranty period	1 y
last modified:	08/12/2017