

*** SPARE PART*** SIMATIC S7, TD 200 TEXT DISPLAY FOR S7-200, 2 LINES, WITH CABLE (2.5M) AND MOUNTING ACCESSORIES

Display

Design of display	LCD backlit
Line display	
• Number of lines	2
• Number of characters per line	20; 20 characters/line: ASCII, cyrillic; 10 characters/line: Chinese
• Character size	5 mm

Supply voltage

Rated value (DC)	24 V; Power supply via the S7-200 communications interface or optional external power supply unit; the CPU sensor power supply (24 V DC) is not subjected to load
------------------	---

Input current

Current consumption, max.	120 mA
---------------------------	--------

Interfaces

Point-to-point	
• Transmission rate, max.	187.5 kbit/s; 9,6 / 19,2 / 187,5 kbit/s

1. Interface

Physics	RS 485
Functionality	
• PPI	Yes; for setting up a network with max. 126 nodes (S7-200, OP, TP, TBP, PG/PC)
— Number of nodes, max.	126

Degree and class of protection

IP (at the front)	IP65
-------------------	------

Ambient conditions

Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C

Dimensions

Width	148 mm
Height	76 mm

Depth	27 mm
Mounting cutout, width	138 mm
Mounting cutout, height	68 mm
Cabinet/switchboard thickness	0.3 mm; 0.3 to 4 mm

Weights

Weight, approx. 250 g

last modified: 08/12/2017