

### Product type designation

### CP 343-1 Advanced

Communications processor CP 343-1 Advanced for connection of SIMATIC S7-300 to Industrial Ethernet: PROFINET IO Controller, PROFINET CBA, ISO, TCP/IP and UDP, S7 communication, fetch/write, SEND/RECEIVE, with and without RFC1006, HTTP with JAVA, Multicast, chargeable Communication modules, HTML diagnostics, FTP Client/Server Email, SNMP, DHCP, NTP-CPU Sync, 10/100 MBit, nur RJ45 connection



### Transfer rate

#### Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

### Interfaces

#### Number of interfaces / acc. to Industrial Ethernet

1

#### Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

1

1

#### Type of electrical connection

- of Industrial Ethernet interface
- at the 1st interface / acc. to Industrial Ethernet

RJ45 port

RJ45 port

#### Type of electrical connection

- for power supply

2-pole plugable terminal block

#### design of the removable storage / C-PLUG

Yes

### Supply voltage, current consumption, power loss

#### Type of voltage / of the supply voltage

DC

#### Supply voltage / 1 / from backplane bus

5 V

|   |        |
|---|--------|
| Supply voltage                                  | 24 V   |
| Supply voltage / external                       | 24 V   |
| Supply voltage / external / at DC / Rated value | 24 V   |
| Relative positive tolerance / at DC / at 24 V   | 20 %   |
| Relative negative tolerance / at DC / at 24 V   | 15 %   |
| Consumed current                                |        |
| • from backplane bus / at DC / at 5 V / typical | 0.14 A |
| Power loss [W]                                  | 14.7 W |

#### Ambient conditions

|  |                |
|--|----------------|
| Ambient temperature  |                |
| • for vertical installation / during operation                 | 0 ... 40 °C    |
| • for horizontally arranged busbars / during operation         | 0 ... 60 °C    |
| • during storage   | -40 ... +70 °C |
| • during transport   | -40 ... +70 °C |
| Relative humidity  |                |
| • at 25 °C / without condensation / during operation / maximum | 95 %           |
| Protection class IP  | IP20           |

#### Design, dimensions and weights

|                        |                                    |
|------------------------|------------------------------------|
| Module format          | Compact module S7-300 double width |
| Width                  | 80 mm                              |
| Height                 | 125 mm                             |
| Depth                  | 120 mm                             |
| Net weight             | 0.8 kg                             |
| Mounting type          |                                    |
| • S7-300 rail mounting | Yes                                |

#### Performance data / open communication

|   |          |
|---|----------|
| Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum           | 16       |
| Amount of data  |          |
| • as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum        | 8 Kibyte |
| • as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum | 8 Kibyte |
| • as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum        | 8 Kibyte |

|   |          |
|---|----------|
| <ul style="list-style-type: none"> <li>• as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum</li> </ul> | 2 Kibyte |
| Number of Multicast stations  | 16       |

#### Performance data / S7 communication

|   |    |
|---|----|
| Number of possible connections / for S7 communication       |    |
| <ul style="list-style-type: none"> <li>• maximum</li> </ul> | 16 |

#### Performance data / multi-protocol mode

|   |    |
|---|----|
| Number of active connections / with multi-protocol mode | 48 |
|---|----|

#### Performance data / IT functions

|  |            |
|--|------------|
| Number of possible connections   |            |
| <ul style="list-style-type: none"> <li>• as client / by means of FTP / maximum</li> </ul>  | 10         |
| <ul style="list-style-type: none"> <li>• as server / by means of FTP / maximum</li> </ul>  | 2          |
| Number of possible connections   |            |
| <ul style="list-style-type: none"> <li>• as server / by means of HTTP / maximum</li> </ul> | 4          |
| <ul style="list-style-type: none"> <li>• as e-mail client / maximum</li> </ul>             | 1          |
| Amount of data / as user data for email / maximum  | 8 Kibyte   |
| Storage capacity / of the user memory  |            |
| <ul style="list-style-type: none"> <li>• as flash memory file system</li> </ul>            | 28 Miabyte |
| <ul style="list-style-type: none"> <li>• as RAM</li> </ul>                                 | 30 Miabyte |
| Number of possible write cycles / of the flash memory cells                                | 100000     |

#### Performance data / PROFINET communication / as PN IO controller

|  |           |
|--|-----------|
| Number of PN IO devices / on PROFINET IO controller / usable / total   | 125       |
| Number of external PN IO lines / with PROFINET / per rack  | 1         |
| Amount of data   |           |
| <ul style="list-style-type: none"> <li>• as user data for input variables / as PROFINET IO controller / maximum</li> </ul>                   | 4 Kibyte  |
| <ul style="list-style-type: none"> <li>• as user data for input variables / as PROFINET IO controller / maximum</li> </ul>                   | 4 Kibyte  |
| <ul style="list-style-type: none"> <li>• as user data for input variables per PN IO device / as PROFINET IO controller / maximum</li> </ul>  | 1433 byte |
| <ul style="list-style-type: none"> <li>• as user data for output variables per PN IO device / as PROFINET IO controller / maximum</li> </ul> | 1433 byte |

#### Performance data / PROFINET CBA

|  |      |
|--|------|
| Number of remote connection partners / with PROFINET CBA | 64   |
| Number of connections / with PROFINET CBA / total        | 1000 |

|   |           |
|---|-----------|
| Amount of data  |           |
| <ul style="list-style-type: none"> <li>• as user data for digital inputs / with PROFINET CBA / maximum</li> </ul>   | 8 Kibyte  |
| <ul style="list-style-type: none"> <li>• as user data for digital outputs / with PROFINET CBA / maximum</li> </ul>  | 8 Kibyte  |
| <ul style="list-style-type: none"> <li>• as user data for arrays and data types / in the case of acyclic transmission / with PROFINET CBA / maximum</li> </ul>  | 8 Kibyte  |
| <ul style="list-style-type: none"> <li>• as user data for arrays and data types / with PROFINET CBA / with cyclical transfer / maximum</li> </ul>               | 450 byte  |
| <ul style="list-style-type: none"> <li>• as user data for arrays and data types / with PROFINET CBA / in the case of local interconnection / maximum</li> </ul> | 2400 byte |

#### Performance data / PROFINET CBA / remote connection / with acyclic transmission

|  |          |
|--|----------|
| Refresh time / of the remote interconnections / in the case of acyclic transmission / with PROFINET CBA  | 100 ms   |
| Number of remote connections to input variables / in the case of acyclic transmission / with PROFINET CBA / maximum  | 128      |
| Number of remote connections to output variables / in the case of acyclic transmission / with PROFINET CBA / maximum   | 128      |
| Amount of data   |          |
| <ul style="list-style-type: none"> <li>• as user data for remote interconnections with input variables / in the case of acyclic transmission / with PROFINET CBA</li> </ul>  | 8 Kibyte |
| <ul style="list-style-type: none"> <li>• as user data for remote interconnections with output variables / in the case of acyclic transmission / with PROFINET CBA</li> </ul> | 8 Kibyte |

#### Performance data / PROFINET CBA / remote connection / with cyclic transmission

|   |           |
|---|-----------|
| Refresh time / of the remote interconnections / with PROFINET CBA / with cyclical transfer  | 8 ms      |
| Number of remote connections to input variables / with PROFINET CBA / with cyclical transfer / maximum  | 200       |
| Number of remote connections to output variables / with PROFINET CBA / with cyclical transfer / maximum   | 200       |
| Amount of data  |           |
| <ul style="list-style-type: none"> <li>• as user data for remote interconnections with input variables / with PROFINET CBA / with cyclical transfer / maximum</li> </ul>  | 2000 byte |
| <ul style="list-style-type: none"> <li>• as user data for remote interconnections with output variables / with PROFINET CBA / with cyclical transfer / maximum</li> </ul> | 2000 byte |

| Performance data / PROFINET CBA / HMI variables via PROFINET / acyclic  |                                  |
|---|----------------------------------|
| Number of connectable HMI stations / for HMI variables / in the case of acyclic transmission / with PROFINET CBA    | 3                                |
| Refresh time / of the HMI variables / in the case of acyclic transmission / with PROFINET CBA                       | 500 ms                           |
| Number of HMI variables / in the case of acyclic transmission / with PROFINET CBA / maximum                         | 200                              |
| Amount of data / as user data for HMI variables / in the case of acyclic transmission / with PROFINET CBA / maximum | 8 Kibyte                         |
| Performance data / PROFINET CBA / device-internal connections   |                                  |
| Number of internal connections / with PROFINET CBA / maximum  | 256                              |
| Amount of data / of the internal connections / with PROFINET CBA / maximum  | 2400 byte                        |
| Performance data / PROFINET CBA / connections to constants  |                                  |
| Number of connections with constants / with PROFINET CBA / maximum  | 200                              |
| Amount of data / as user data for interconnections with constants / with PROFINET CBA / maximum                     | 4096 byte                        |
| Performance data / PROFINET CBA / PROFIBUS proxy functionality  |                                  |
| Product function / with PROFINET CBA / PROFIBUS proxy functionality   | No                               |
| Performance data / telecontrol  |                                  |
| Protocol / is supported   |                                  |
| • TCP/IP  | Yes                              |
| Product functions / management, configuration, engineering  |                                  |
| Product function / MIB support  | Yes                              |
| Protocol / is supported   |                                  |
| • SNMP v1   | Yes                              |
| • DCP   | Yes                              |
| • LLDP  | Yes                              |
| Configuration software  |                                  |
| • required  | STEP 7 V5.3 SP2 or higher        |
| • for PROFINET CBA / required   | SIMATIC iMap V2.0 SP1 and higher |
| Identification & maintenance function   |                                  |
| • I&M0 - device-specific information  | Yes                              |
| • I&M1 – higher-level designation/location designation  | Yes                              |
| Product functions / Diagnostics   |                                  |
| Product function / Web-based diagnostics  | Yes                              |

## Product functions / Switch

|                          |    |
|--------------------------|----|
| Product feature / Switch | No |
|--------------------------|----|

## Product functions / redundancy

|                   |    |
|-------------------|----|
| Product function  |    |
| • Ring redundancy | No |

## Product functions / Security

|  |     |
|--|-----|
| Product function                               |     |
| • ACL - IP-based                               | Yes |
| • ACL - IP-based for PLC/routing               | No  |
| • switch-off of non-required services          | No  |
| • Blocking of communication via physical ports | No  |
| • log file for unauthorized access             | No  |

## Product functions / time

|   |     |
|---|-----|
| Product function / SICLOCK support              | Yes |
| Product function / pass on time synchronization | Yes |
| Protocol / is supported                         |     |
| • NTP   | Yes |

## Further information / Internet-Links

|   |   |
|---|---|
| Internet-Link                                     |   |
| • to website: Selector SIMATIC NET SELECTION TOOL | <a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>                               |
| • to website: Industrial communication            | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>                 |
| • to website: Industry Mall                       | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                   |
| • to website: Information and Download Center     | <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> |
| • to website: Image database                      | <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>             |
| • to website: CAx Download Manager                | <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                 |
| • to website: Industry Online Support             | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>             |

## Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

04/02/2020