

Product data sheet

Characteristics

ASISSLC2

AS-Interface -for product with connector - 1 cable entry M12

Price** : 90.00 USD



⚠ Discontinued

Commercial status

Discontinued: 31 December 2015

End-of-service: 31 December 2020

ASISSLC2 has not been replaced. Please contact your customer care center for more information.

Main

Product or component type	Interface for products with connector
Range compatibility	AS-Interface cabling system
Cable entry	2 entries M12
Number of contacts	2
AS-Interface	0.B.F.F
Supply	Via AS-Interface

Complementary

Addressing	Using adjustment terminal
[Us] rated supply voltage	24 V DC - 15...15 %
Power consumption in W	1.2 W
Current consumption	45 mA AS-Interface line
Connections - terminals	AS-Interface line 1 connector M12
Net weight	0.11 lb(US) (0.05 kg)

Environment

Standards	EN 954-1 category 4 EN/IEC 60947-5-1 EN/IEC 60204-1 ISO 13849-1 category 4
Product certifications	CSA UL TÜV
IP degree of protection	IP67 IEC 60529
Ambient air temperature for operation	14...131 °F (-10...55 °C)
Ambient air temperature for storage	-13...185 °F (-25...85 °C)
Shock resistance	10 gn
Vibration resistance	5 gn

Ordering and shipping details

Category	18340-AS-I SAFE PRODUCTS (SPX2)
Discount Schedule	SPX2

GTIN	00785901602934
Returnability	No
Country of origin	FR

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------