



ⓘ Discontinued

Main

Range of product	Altivar 66
Product or component type	Variable speed drive

Complementary

Product destination	Asynchronous motors
[Us] rated supply voltage	380...460 V - 10...10 %
Supply frequency	50...60 Hz - 5...5 %
Network frequency	47.5...63 Hz
Network number of phases	3 phases
Motor power kW	5.5 kW at 380...460 V
Motor power hp	7.5 hp
Line current	24.4 A at 380 V 19.5 A at 460 V
Apparent power	7.2 kVA at 400 V
Continuous output current	10.5 A at 400 V
Output frequency	0...0.3 kHz
Nominal switching frequency	2.5 kHz
Switching frequency	0.5...4 kHz 8...16 kHz with current derating
Local signalling	1 graphic display terminal
Output voltage	400 V
Communication port protocol	Modbus
Physical interface	RS485 multidrop serial link
Transmission rate	9.6...19.2 kbauds
Height	295 mm
Width	200 mm
Depth	165 mm
Option card	Communication card for Profibus DP Communication card for CANopen Communication card for DeviceNet Communication card for Ethernet Communication card for Fipio Communication card for Uni-Telway

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Communication card for Interbus-S
Communication card for Modbus Plus
Communication card for AS-Interface

Environment

IP degree of protection	IP00
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...70 °C
Operating altitude	<= 1000 m > 1000...2000 m 1 % per 100 m

Packing Units

Package 1 Weight	6528.000 g
Package 1 Height	260.000 mm
Package 1 width	290.000 mm
Package 1 Length	385.000 mm

ATV66U72N4 is replaced by:



Variable speed drives ATV71HU40N4

variable speed drive ATV71 - 4kW-5HP - 480V - EMC filter-graphic terminal

Qty 1

Reason for Substitution: End of life | Substitution date: 01 April 2005
