


DATASHEET

Modbus Serial Lite Communication Module MVI69L-MBS

The MVI69L-MBS, Modbus Serial module for the CompactLogix™ series of controllers is designed for smaller applications where communication between a few Modbus Serial devices is required. This module has an Add-on Profile and an Add-on Instruction to reduce commissioning time. The MVI69L-MBS has a single serial port and can support either Master or Slave connectivity to interface with a variety of devices using the Modbus Protocol.



Features

- ◆ Supports CompactLogix processors with 1769 I/O bus capability version 16 and greater (MicroLogix 1500 not supported)
- ◆ Add-on Instruction creates UDTs, providing logical definitions for I/O, status, and control data
- ◆ Add-on Profile support, improving integration in the CompactLogix System
- ◆ Diagnostic data available in processor controller tags, enabling decisions to be made based upon node health
- ◆ Module configuration backed up in CompactLogix project (ACD file)
- ◆ Module acts as a co-processor reducing impact to PLC scan time
- ◆ Supports up to 240 words of I/O data
- ◆ Application port can be configured as either a Modbus Master or Modbus Slave
- ◆ Supports up to 30 Modbus Commands as a Modbus Master
- ◆ Supports Enron and Daniel style Floating point data implementations
- ◆ Most suitable for OEM and Machine Builder applications

General Specifications

Configuration	ProSoft Configuration Builder	
I/O Size	240/240 - 16 bit integers	
Communication parameters	Baud Rate: 110 to 115K baud Stop Bits: 1 or 2 Data Size: 7 or 8 bits Parity: None, Even, Odd RTS Timing delays: 0 to 65535 milliseconds	
Modbus Modes	RTU mode (binary) with CRC-16 ASCII mode with LRC error checking	
Floating Point Data	Floating point data movement supported, including configurable support for Enron, Daniel [®] , and other implementations	
Modbus Function Codes Supported	1: Read Coil Status 2: Read Input Status 3: Read Holding Registers 4: Read Input Registers 5: Force (Write) Single Coil 6: Preset (Write) Single Holding Register 8: Diagnostics (Slave Only, Responds to Subfunction 00)	15: Force(Write) Multiple Coils 16: Preset (Write) Multiple Holding Registers 17: Report Slave ID (Slave Only) 22: Mask Write Holding Register (Slave Only) 23: Read/Write Holding Registers (Slave Only)

Functional Specifications

Modbus Master

A port configured as a Modbus Master actively issues Modbus commands to other nodes on the Modbus network.

Command List	Up to 30 commands, each fully configurable for function, slave address, register to/from addressing and word/bit count.
Polling of command list	Configurable polling of command list, including continuous and on change of state.
Status Data	Error codes available on an individual command basis. A slave status list is maintained on an active Modbus Master port.

Modbus Slave

A port configured as a Modbus Slave permits a remote Master to interact with all data contained in the module.

Node address	1 to 247 (software selectable)
Status Data	Error codes, counters and port status available on an active Modbus Slave port



Where Automation
Connects™

Global Distribution

ProSoft Technology[®] products are distributed and supported worldwide through a network of over 500 distributors in over 50 countries. Our knowledgeable distributors are familiar with your application needs. For a complete list of distributors, go to our web site at:

www.prosoft-technology.com

Global Support

We are there for you

All ProSoft Technology products are backed with free, unlimited technical support and a three year warranty. Contact our worldwide Technical Support team directly by phone or email.

Global Offices

We are where you are

ProSoft Technology has regional offices worldwide available to help you with all your industrial application needs. If you need help choosing a ProSoft Technology solution for your particular application check out our contact information under distributor sales on the web site at:

www.prosoft-technology.com

Whether your application is large or small, our technical professionals are there to help you choose the right communication solution.

Hardware Specifications

Specification	Description
Dimensions	Standard 1769 Single-slot module
Current Load	450 mA max @ 5 VDC Power supply distance rating of 4
Operating Temp.	32° F to 140° F (0° C to 60° C)
Storage Temp.	-40° F to 185° F (-40° C to 85° C)
Relative Humidity	5% to 95% (with no condensation)
LED Indicators	OK - Module Status ETH - Ethernet Communication P1 - Serial Communication BP - Backplane Connectivity CFG - Valid Configuration
Debug Port	10/100 Ethernet Port
App Ports (P1)	RS-232, RS-485 or RS-422 RJ45 (DB-9F with supplied cable) RS-232 handshaking configurable 500V Optical isolation from backplane
Shipped with Unit	1 - RJ45 to DB-9M cables for application port 1 - DB-9F breakout boards

Agency Approvals and Certifications

Please visit our website: www.prosoft-technology.com



Additional Products

ProSoft Technology® offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms. For a complete list of products, visit our web site at: www.prosoft-technology.com

Ordering Information

To order this product, please use the following:

Modbus Serial Lite Communication Module

MVI69L-MBS

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to: www.prosoft-technology.com and select *How to Buy* from the menu.

Copyright © 2019 ProSoft Technology, Inc.
All rights reserved. 4/25/2019

Specifications subject to change without notice.